

расчетный диаметр d_d (мм)	кол-во канавок k	тип	вес (≈кг)	Отверстие $d_{\text{макс}}$ (мм)	длина ступицы l (мм)	расчетный диаметр d_d (мм)	кол-во канавок k	тип	вес (≈кг)	Отверстие $d_{\text{макс}}$ (мм)	длина ступицы l (мм)
SPA/13											
50	1		0,300	18	34	106	1		0,900	28	34
	2		0,500	18	49		2		1,700	28	49
	3		0,600	18	47		3		2,200	32	42
56	1		0,400	20	34		4		3,200	32	53
	2		0,600	20	49		5		3,900	35	60
63	1		0,500	25	34	112	1		1,100	28	34
	2		0,800	25	49		2		1,800	38	49
	3		0,900	25	47		3		2,400	38	42
71	4		1,200	25	60		4		3,400	42	53
	5		1,500	25	70		5		4,000	42	60
75	1		0,500	25	34	118	1		1,100	32	34
	2		0,900	28	49		2		1,800	38	49
	3		1,000	32	42		3		2,400	42	42
	4		1,500	32	60		4		3,400	42	53
	5		1,800	32	70		5		4,100	48	65
80	1		0,500	24	34	125	1		1,400	32	34
	2		1,000	24	49		2		1,900	38	49
	3		1,100	24	42		3		2,600	42	42
	4		1,800	24	60		4		3,500	42	53
	5		1,900	28	82		5		4,400	48	65
85	1		0,600	28	34	132	1		1,500	32	34
	2		1,000	32	49		2		2,200	38	49
	3		1,200	38	42		3		2,600	42	42
	4		1,900	38	60		4		3,600	42	53
	5		2,000	38	55		5		4,800	48	65
90	1		0,600	24	34	140	1		1,500	32	34
	2		1,200	28	49		2		2,300	38	49
	3		1,400	28	42		3		2,600	42	42
	4		2,000	28	53		4		3,700	42	53
	5		2,200	32	55		5		5,000	48	65
95	1		0,900	28	34	150	1	x	1,600	38	36
	2		1,500	32	49		2	x	2,600	38	49
	3		1,600	38	42		3		3,000	42	42
	4		2,200	42	53		4		4,000	42	53
	5		2,500	42	67		5		5,200	48	65
100	1		0,800	28	34	160	1	x	1,800	38	36
	2		1,600	28	49		2	x	2,400	38	49
	3		1,900	28	42		3	x	2,800	42	42
	4		2,500	32	53		4		3,600	48	60
	5		2,800	35	67		5		5,500	48	70
106	1		0,800	28	34	170	1	x	2,000	35	36
	2		1,400	32	49		2	x	2,900	35	49
	3		2,000	38	42		3	x	3,200	35	42
	4		2,700	42	53		4	x	4,200	35	60
	5		3,100	42	60		5	x	5,800	38	70
112	1		0,800	28	34	180	1	x	2,000	38	36
	2		1,400	32	49		2	x	3,200	42	49
	3		2,000	38	42		3	x	3,600	42	42
	4		2,700	42	53		4	x	4,700	48	60
	5		3,100	42	60		5	x	6,100	48	70

расчетный диаметр d _c (мм)	кол-во канавок	тип	вес (≈кг)	Отверстие d _{max} (мм)	длина ступицы l (мм)	расчетный диаметр d _c (мм)	кол-во канавок	тип	вес (≈кг)	Отверстие d _{max} (мм)	длина ступицы l (мм)
190	1	x	2,000	38	36	400	1	x	6,900	50	50
	2	x	3,200	42	49		2	x	8,800	55	53
	3	x	4,000	42	42		3	x	10,500	60	47
	4	x	5,200	48	60		4	x	12,400	60	67
	5	x	6,300	48	70		5	x	15,900	60	82
200	1	x	2,400	38	36	450	1	x	7,500	55	50
	2	x	2,900	42	49		2	x	9,400	55	53
	3	x	4,200	48	42		3	x	12,200	60	47
	4	x	5,000	55	60		4	x	14,200	65	67
	5	x	6,500	55	70		5	x	18,300	65	82
212	1	x	2,700	40	36	500	1	x	10,500	55	50
	2	x	3,400	42	49		2	x	10,700	55	55
	3	x	4,400	42	42		3	x	13,500	60	60
	4	x	5,700	42	60		4	x	16,300	65	67
	5	x	6,900	42	70		5	x	22,800	65	82
225	1	x	2,800	40	36	560	1	x	14,000	55	60
	2	x	3,900	42	49		2	x	13,100	55	60
	3	x	4,600	42	42		3	x	15,600	60	74
	4	x	6,500	42	60		4	x	19,400	65	67
	5	x	7,300	42	70		5	x	24,500	65	82
236	1	x	3,300	38	36						
	2	x	4,100	42	49						
	3	x	4,900	48	47						
	4	x	6,200	55	60						
	5	x	7,500	55	70						
250	1	x	3,400	42	36						
	2	x	4,300	48	49						
	3	x	5,300	48	47						
	4	x	7,000	55	60						
	5	x	7,900	60	70						
280	1	x	3,900	42	44						
	2	x	5,400	48	53						
	3	x	6,500	48	47						
	4	x	8,500	55	60						
	5	x	9,900	60	70						
300	1	x	4,300	48	44						
	2	x	5,900	48	53						
	3	x	7,500	55	47						
	4	x	9,800	55	60						
	5	x	11,300	60	70						
315	1	x	4,800	48	44						
	2	x	6,600	48	53						
	3	x	8,800	55	47						
	4	x	11,100	55	60						
	5	x	10,500	60	70						
355	1	x	5,500	48	44						
	2	x	7,700	55	53						
	3	x	9,600	55	47						
	4	x	11,800	55	60						
	5	x	13,800	60	70						

Кол-во канавок z	1	2	3	4	5
Ширина b ₂ (мм)	20	35	50	67	82

x Сплицевый шкив
 Расположение ступицы: с одной стороны заподлицо
 Материал: En -GJL 200 - Dln En 1561

